

## Gradient International Standards Conformity Report

Lens Code:

Production Line:

Operator:

Base:

Note:

Info:

Date:

Time:

Equipment:

S/N:



SOCIETA' EUROPEA LENTI

Additional required information  
This is not suitable for:  
- direct viewing of the sun  
- for use in twilight or at night  
- protection against sources of radiation other

### American National Standard ANSI Z80.3-2018

Center	Up	Down
Luminous Transmittance (Tv) %		
30,16	20,69	48,99

Primary Function:


Warnings:

### International Standard ISO 12312-1:2013/Amd.1:2015

Center	Up	Down
Luminous Transmittance (Tv) %		
30,21	20,72	49,08

Filter Category:

Descriptive Label:


Warnings:  

### Australian/New Zealand Standard AS/NZS 1067.1:2016

Center	Up	Down
Luminous Transmittance (Tv) %		
30,21	20,72	49,08

Filter Category:

Descriptive Label:

Warnings:  

#### VISIBLE SPECTRAL RANGE

Traffic signal transmittance %

Color	Center	Up	Down	Min	Max	Result
Red	20,69	14,82	32,34	8,00	3,00	PASS
Yellow	27,33	18,55	45,08	6,00	3,00	PASS
Green	32,08	22,14	51,68	6,00	3,00	PASS

Spectral transm (475-650) (Tv)

Center	Up	Down	Min	Max	Result
0,57	0,55	0,60	0,20	0,20	PASS

#### VISIBLE SPECTRAL RANGE

Detection of signal light: **INCANDESCENT LIGHT**

Color	Center	Up	Down	Min	Max	Result
QRed	0,76	0,77	0,76	0,80	0,80	FAIL
QYellow	0,92	0,91	0,93	0,60	0,60	PASS
QGreen	1,05	1,06	1,05	0,60	0,60	PASS
QBlue	1,10	1,14	1,06	0,60	0,60	PASS

Spectral transm (475-650) %

Center	Up	Down	Min	Max	Result
17,29	11,30	29,21	6,04	6,04	PASS

#### VISIBLE SPECTRAL RANGE

Detection of signal light: **INCANDESCENT LIGHT**

Color	Center	Up	Down	Min	Max	Result
QRed	0,76	0,77	0,76	0,80	0,80	FAIL
QYellow	0,92	0,91	0,93	0,60	0,60	PASS
QGreen	1,05	1,06	1,05	0,60	0,60	PASS
QBlue	1,10	1,14	1,06	0,70	0,70	PASS

Spectral transm (475-650) %

Center	Up	Down	Min	Max	Result
17,29	11,30	29,21	6,04	6,04	PASS

#### UV SPECTRAL RANGE

Mean EUV (280-315) %

Center	Up	Down	Max	Limit	Result
0,18	0,05	0,00	3,77	3,77	PASS

Mean NUV (315-380) %

Center	Up	Down	Max	Limit	Result
0,27	0,09	0,00	30,16	30,16	PASS

BlueLight Tsb (380-500) %

Center	Up	Down
33,10	24,14	49,53

#### UV SPECTRAL RANGE

Tsuva (315-380) %

Center	Up	Down	Max	Limit	Result
0,26	0,09	0,00	15,10	15,10	PASS

Tsubv (280-315) %

Center	Up	Down	Max	Limit	Result
0,18	0,04	0,00	1,51	1,51	PASS

Tsuv (280-380) %

Center	Up	Down
0,23	0,07	0,00

Tsb (380-500) %

Center	Up	Down
33,10	24,14	49,53

#### UV SPECTRAL RANGE

Tsuva (315-400) %

Center	Up	Down	Max	Limit	Result
0,25	0,08	0,00	15,10	15,10	PASS

Tsubv (280-315) %

Center	Up	Down	Max	Limit	Result
0,18	0,04	0,00	1,51	1,51	PASS

Tsuv (280-400) %

Center	Up	Down
0,22	0,07	0,00

Tsb (380-500) %

Center	Up	Down
33,10	24,14	49,53

#### COLOR LIMITS

Color	X	Y	Result
Green	0,198	0,388	PASS
Yellow	0,556	0,442	PASS
D65	0,283	0,321	PASS

See color Limit of acceptance on a CIE (1931) chromatic diagram

#### COLOR LIMITS

Color	X	Y	Result
Green	0,198	0,388	PASS
Yellow	0,556	0,442	PASS
D65	0,283	0,321	PASS

#### COLOR LIMITS

Color	X	Y	Result
Green	0,198	0,388	PASS
Yellow	0,556	0,442	PASS
D65	0,283	0,321	PASS

